

GLOBAL BD

TOGETHER WE ACHIEVE THE EXTRAORDINARY

220 West Parkway, Unit 8 - Pompton Plains, NJ 07444 Tel: 973-831-5866 www.globalbd.com

LED 90W WALL PACK | Model # GBD-90W-WP-SA-5K



90w |Color 5000 | Lumens 6000
Aluminum |Frosted Lens | Series W

Heavy duty die-cast aluminum housing, fully sealed to be dirt and bug proof. High quality tempered glass optics. Integral secondary heat sink to optimize thermal transfer and maximize performance and life of LED.

TECHNICAL SPECIFICATIONS

MODEL: GBD-WP-90W-WP-SA-5.7K	LISTED: cETLus, FCC, DLC
VOLTAGE: AC100-277V	POWER FACTOR: 0.904
FREQUENCY: 50/60 Hz	LUMENS: 6000LM
LUMENS EFFICACY: 71.96LM/W	KELVIN (CCT): 5,000K
THD: 16.03%	CRI: 86.2
IP RATING: IP65	WATTAGE: 90 W
BEAM ANGLE (DEGREE): 95°	MATERIALS: Aluminum Alloy + Borosilicate Glass
POWER: External	LED CHIPS: smd 3030
LIFE SPAN (HOURS): 50,000 Hours	DIMMING : Yes
LENGTH OF WARRANTY (YEARS): 5 Years Standard	PRODUCT LENGTH: 363 x 231 x 188mm
MOUNTING: Build-in/Suspended/Surface Mount	WORKING ENVIRONMENT: -20°C to 50°C (-4°F to 122°F)
STORAGE HUMIDITY: 45 - 50%	OPERATING HUMIDITY: 20%-70% RH
STORAGE TEMP: -30°C to 80°C	APPLICATION: OUTDOOR
PERCENTAGE OF WATTAGE SAVED: 45 - 50%	

